



NAVARAPART NP300 D23 NAVARA AIR BOX SAVER BRACKET KIT INSTRUCTIONS

SKU: PAP-0140-KIT



Remove lid of airbox from vehicle, then remove filter, and airbox base. (please note these instructions were done on a car fitted with Safari Snorkel, so the airbox was able to be lifted up while still fitted in car)



Fit bracket over the top of the two locating lugs. (you may need to remove cable ties in some models) Push bracket all the way in, and all the way up to ensure correct fitment. It is meant to be a tight fit!



Drill the two circled holes through the plastic locating bracket with a 5.5mm drill bit. You can take these out to 6mm once the bracket is removed if you feel the need. Next, deburr the holes inside and out. Using a larger drill bit gently is a good way to clean the face up, then you can access the back side of the hole and carefully scrape the burrs off with a flat blade screwdriver or file.



Fit the two speed nuts over the top of the two drilled holes, with the raised part at the front side. You may need to spread the opening of the speed nuts a bit to get them on. You can use a flat blade screwdriver for this. We find the easiest way is to spread the speed nuts a little, then fit to the brackets with a pair of multi-grips as pictured.



Fit the bracket with the two provided screws and insert the replacement cable ties, for holding the wiring loom.



Test fit the filter and lid to the base before fitting into car. It should be a firm fit, then reinstall in to the car. Remember to tie up the wiring as best you can. If you have any issues, call us on (03) 9735 9099 or email sales@patrolapart.com.au